

Model SC52E Versatap Specification Sheet

Enjoy instant filtered steaming hot and cool drinking water from this stylish sink mixer.

- Up to 60 cups an hour of steaming hot water, integrated into the sink mixer.
- Unlimited cool filtered drinking water.
- Electronic temperature adjustment with Easy-to-read LCD screen.
- Easy-change filters with easy-access shut-off valve.
- High capacity filter ensures great water flow.



INSTALLATION PRE-REQUIREMENTS

Power Supply

- A standard 10amp 3pin power outlet conveniently placed within 1m of the intended location of the boiler tank. This must be installed by a qualified electrician.

Water Supply

- A standard Cold water supply fitted with a 15mm stop tap situated within easy access of the intended location of the boiler tank. This must be installed by a qualified plumber.
- Sink mixer also requires a standard 15mm hot and cold water feeds.
- Supply water pressure must not exceed 10,000kpa with pressure regulator installed.
- Water supply must be microbiologically safe.

Dispenser Mounting

- The sink mixer is easily installed through a standard 35mm hole.

Drip Tray

- As your Schwan appliance is always full of hot water, we recommend a drained drip tray be used in those applications where any leakage could cause property damage.

Warranty

- Two-year repair or replacement warranty for residential installations. One-year repair or replacement warranty for commercial installations (maximum 6 staff).

Certifications

- Schwan drinking water appliances have been laboratory tested and certified to comply with AS/NZS 60335.1 and AS/NZS 60335.2.15 standards.

SPECIFICATIONS

Model	SC52E	Voltage	230V ~50Hz
Description	Steaming Hot & Cool Filtered Drinking Water plus Sink Mixer Functions	Power Input	1300W
Cups / Hour	60	Tank Capacity	2.4L
Unit Size:		Inlet Water Pressure:	
Height	302mm	Minimum	240 kpa
Width	200mm	Maximum	700 kpa
Depth	232mm	Complies with standards:	
			AS/NZS 60335.1
			AS/NZS 60335.2.15

Model SC52E Specification Sheet

